



Professional double channel rear view kit for the surveillance of partially or totally blind areas. System provides a panoramic high resolution vision also in absence of light.

- ✓ **HIGH QUALITY IMAGE**
- ✓ **SUITS TO A WIDE RANGE OF INDUSTRIAL VEHICLES**
- ✓ **WATERPROOF IR BALL CAMERA**
- ✓ **COMPACTNESS FOR EASY ON-BOARD INTEGRATION**



System provides an integrated DC/DC converter for maximum versatility. The system architecture, with all the connection with the vehicle starting from the powerbox, makes installation quick and easy. The pre-made molded connection between the modules guarantee the maximum connection reliability.

KIT CONTENT

Monitor kit inclusive of:

- 5" monitor;
- universal bracket.

Camera kit inclusive of:

- IR Ball camera;
- 3 m connecting cable;
- bracket, screws, bolts, washers kit.

Powerbox kit inclusive of:

- powerbox/splitter with channel change and voltage reduction function.

GENERAL FEATURES

Operating voltage	12-48VDC
Triggering voltage	12-48VDC
Operating current	500mA max
Number of cameras (max)	2 (with automatic triggering)
Operating temperature	-30°C / +70°C

MONITOR TECHNICAL FEATURES

Screen dimensions	5"
TFT	TFT
Ratio	4:3
Resolution	307x200 pixels
Brightness	200 cd/m ²
Outline dimensions	126.5mm x 100mm x 15mm
IP rating	IP50

CAMERA TECHNICAL FEATURES

View angle	110°
Resolution	500x582 pixels
IP rating	IP68
Night view	15 infrared leds
Night view distance	8m max